

BenchMixer™

Benchmark Vortex Mixer



- Powerful Motor for **INSTANT** Vortexing
- Q-Drive™ Dynamic Balance System
- Touch or Continuous Operation
- Variable Speed Control from 200 to 3200rpm



BV1000-FLAT



BV1000-COMBO

Technical Data

Speed Range:	200 to 3200 rpm
Operating Modes:	Touch or continuous
Operating Temp. Range:	+4 C to +65 C
Dimensions:	13 x 16 x 17 cm 5 x 6.3 x 6.7 in.
Weight:	3.8 kg / 8.4 lb
Electrical:	115V AC, 60 Hz, 1.5A 230V AC, 50 Hz, 0.75A
Warranty:	2 years

The BenchMixer™ sets the new standard in vortex mixing. With advanced Q-Drive™ technology, the BenchMixer™ provides smooth instant vortexing of even the largest sample sizes, including full 50ml tubes. The unique counter balance system creates maximum vortexing action, while minimizing noise and excessive vibration. This results in quieter, more efficient and longer lasting operation.

Other features include: “no-walk” suction feet, cold room/incubator compatibility and spill-proof electronic controls.

Ordering Information

BV1000* **BenchMixer Vortex Mixer**

BV1000-FLAT	Optional 3 inch flat head
BV1000-COMBO	Optional combination head for tubes and microplates. Holds 66 tubes (38 x 1.5ml and 28 x 0.5ml) or one microplate

* To order a product in 230V, please add -230 to item number.

Benchmark
Scientific

Benchmark Scientific Inc.
PO Box 709
Edison, NJ 08817
Phone: 908-769-5555
Fax: 908-222-1864
Web: www.BenchmarkScientific.com
Email: Info@BenchmarkScientific.com